



1000Vdc Isolation Twin Output 1 Watt Dc-Dc Converter



FEATURES:

- 14PIN DIL Package
- High Efficiency up to 85%
- Internal SMD Construction
- Unregulated Output Types
- Operating Temperature:-40°C TO +85°C
- No External Component Required ● Industry Standard Pinout



Specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified

Part Number	Output2		Efficiency
	Voltage (VDC)	Current (mA)	%TYP
25D-XXDXX03NNL	3.3	150	70
25D-XXDXX05NNL	5	100	75
25D-XXDXX09NNL	9	56	75
25D-XXDXX12NNL	12	42	75
25D-XXDXX15NNL	15	34	75
25D-XXDXX24N2NL	24	21	75

Note:1."XX" Is Voltage:03=3.3Vdc,05=5Vdc,09=9Vdc 12=12Vdc,15=15Vdc,24=24Vdc.

2. 3.3V for output only, not for input.

3. The input voltage increases, there will be an increase in efficiency.

4. Over 24Vdc input voltage or Output voltage, using the 2nd package

Input Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Tolerance	Vo, Io Nom			±5	%
Filter	Capacitor				

Output Specifications


Parameters	Conditions	Min	Typ	Max	Units
Voltage Tolerance	100% full load			±5	%
Short Circuit Protection	Short Term			1 Sec	
Line Regulation	For 1.0% OF Vin		1.2		%
Load Regulation	3.3V,5V (10% To 100% F.L)			15	%
Load Regulation	9V,12V,15V,24V (10% To 100% F.L.)			10	%
Ripple & Noise	BW=DC To 20MHz			100	mVp-p
Transient response setting time	50% load step change		350		us

General Specifications

Parameters	Conditions	Min	Typ	Max	Units
Isolation Resistance	500Vdc	1000			MΩ
Switching Frequency	Full load,nominal input		100		KHz
Operating Temperature		-40		+85	°C
Humidity	Non Condensing			95	%
Cooling	Free air Convection				
Case material	DAP				
MTBF	MIL-HDBK-217F@25°C	3500000			Hours
Weight			2.3 or 2.8		g
Dimensions			20.32x10.16x6.80		mm
Dimensions			20.32x10.16x7.70		mm



1000Vdc Isolation Twin Output 1 Watt Dc-Dc Converter



Recommended Test Circuit

5V :Cin 4.7uF,25V 3.3V :Cout 22uF,25V
 9V :Cin 4.7uF,25V 5V :Cout 10uF,25V
 12V :Cin 2.2uF,25V 9V :Cout 4.7uF,25V
 15V :Cin 1uF,50V 12V :Cout 2.2uF,25V
 24V :Cin 1uF,50V 15V :Cout 1uF,50V
 24V :Cout 1uF,50V

Part Number

25D - 12 D 0505 N NL

A B C D E F

A:Series
 B:Input Voltage
 C:Dual Output
 D:Output Voltage
 E:Unregulated(N)
 F:RoHS Version

Markings and Dimensions

Unit: mm Unless otherwise specified, all tolerances are ± 0.25

Packaging

Size(mm)		
A	B	C
13.23	12.30	530

PIN Connection

PIN	1	7	8	9	10	11	14
DUAL	-Vin	NC	-Vout2	+Vout2	-Vout1	+Vout1	+Vin