

P6CG-xxxxZSLF



PM2-SERIES

Rev.02-2009

- ✓ 1 Watt
- ✓ Regulated
- ✓ **Dual Split Output**
- ✓ **SIP7 Case**
- ✓ **1 kV DC I/O Isolation**
- ✓ **Low Ripple and Noise**

The PM2 series P6CG-xxxxZSLF is a family of cost effective 1 W regulated dual split output DC/DC converters. These converters are in an ultra miniature SIP7 case. Devices are encapsulated. High performance features: Regulated Output, 1000VDC input/output isolation, high efficiency operation, output voltage accuracy of $\pm 2\%$ maximum, input range of $\pm 10\%$ tolerance and low output ripple and noise.

All specifications typical at $T_a=25^\circ\text{C}$, nominal input voltage and full load unless otherwise specified

Input Specifications

Voltage Range	$\pm 10\%$
Input Filter	Capacitors
Input Reflected Ripple Current ¹	20 mA pk-pk

Output Specifications

Voltage Accuracy	$\pm 2\%$
Line Regulation	$\pm 0.4\%$
Load Regulation (0% - 100%)	$\pm 0.3\%$
Ripple and Noise (20Mhz bandwidth)	50 mV pk-pk
Temperature Coefficient	$\pm 0.02\% / ^\circ\text{C}$

General Specifications

Efficiency	See Table
I/O Isolation Voltage (3 sec.)	1000 VDC
I/O Isolation Capacity	60 pF, typ.
I/O Isolation Resistance	1000 M Ohm
Switching Frequency	80 kHz (Variable)
Humidity	95% rel H
Reliability Calculated MTBF (MIL-HDBK-217F)	> 1.121 Mhrs

Physical Specifications

Case Material	Non Conductive Black Plastic (UL94V-0 rated)
Potting Material	Epoxy (UL94V-0 rated)
Weight	~ 2.5g, typ.

Environment Specifications

Operating Temperature	-25 to +71 $^\circ\text{C}$ (ambient)
Maximum Case Temperature	100 $^\circ\text{C}$
Storage Temperature	-40 to +125 $^\circ\text{C}$
Cooling	Free Air Convection (10 mm distance required)
RoHS Conform	Soldering 260 $^\circ\text{C}$, max. (1.5 mm from case 10s.)



Selection Guide

Dual Split Output

Order #	Input Voltage (VDC)	Input Current No Load (mA)	Input Current Full Load (mA)	Output Voltage (VDC)	Output Current Full Load (mA)	Efficiency (%)	Capacitor Load (uF) ²
DUAL SPLIT OUTPUT							
P6CG-0505ZSLF	5	28	307	5, 5	100, 100	65	100
P6CG-1205ZSLF	12	15	124	5, 5	100, 100	67	100
P6CG-1505ZSLF	15	12	99	5, 5	100, 100	67	100
P6CG-2405ZSLF	24	8	59	5, 5	100, 100	70	100

If you need other specifications, please enquire.

Package / Pinning / Derating



PIN CONNECTIONS	
#	DUAL SPLIT
1	+Vin
2	- Vin
4	+V2 out
5	Ground
6	+ V1 out
7	Omitted

App Notes:

¹ = Measured Input reflected ripple current with a simulated source inductance of 12uH.

² = Tested by minimal Vin and constant resistive load.

- Operation under no-load conditions will not damage these devices, but they will not observe the listed specifications.