



CEB75 SERIES 62 TO 84 WATT 1/8 BRICK DC-DC CONVERTERS

FEATURES

- * 62 - 84W Isolated Output
- * Eighth Brick Package
- * Regulated Outputs
- * Efficiency up to 92%
- * 1500VDC Isolation
- * Input Under Voltage Protection
- * Over Current Protection
- * Over Temperature Protection
- * Remote ON/OFF
- * Safety Meets UL60950-1



MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT		INPUT CURRENT		% EFF.	Capacitor Load max.
			MIN.	MAX.	NO LOAD	FULL LOAD		
CEB75-48S2V5	36-75 VDC	2.5 VDC	0 mA	25A	60 mA	1463mA	89	10000 μ F
CEB75-48S3V3	36-75 VDC	3.3 VDC	0 mA	20A	60 mA	1528mA	90	10000 μ F
CEB75-48S05	36-75 VDC	5.0 VDC	0 mA	15A	50 mA	1736mA	90	10000 μ F
CEB75-48S12	36-75 VDC	12 VDC	0 mA	7A	70 mA	1902mA	92	1500 μ F

NOTE: 1. Nominal Input Voltage 48 VDC

